		HAZARD	INF	HERENT HAZARD LE	VEL	CURRENT CONTROLS	LEGAL AND OTHER REQUIREMENTS	RE	SIDUAL HAZARD L	EVEL	ACCEPTABLE?	ADDITIONAL CONTROLS	IF UNACCEPTABLE
Examples	What is the Hazard?	What could happen?	Likelihood	Consequence	Hazard Score	What are the existing ways this hazard is managed?	What law or standards are associated?	Likelihood	Consequence	Hazard Score	Is the hazard score acceptable? (i.e. only low or medium)	If No what else do you need to do?	Who is responsible?
	Chemicals such as HF, HCN, CO, F2, Me2Hg, benzene, and research chemicals with unknown but potentially harmful properties.	Exposure (workers) leading to serious injury/illness or death through toxic effects, chemical pneumonitis, burns, carcinogenic effects, nano toxicity; uncertainty factor due to regular handling of unexplored research chemicals; significant negative reputation (media)	LIKELY	CATASTROPHIC	EXTREME (24)	Elimination - Wherever possible, alternatives to hazardous chemicals for research purposes are being used over hazardous chemicals. Isolation - Wet laboratories physically segregated from office areas. Where highly hazardous chemicals are deemed necessary, isolated high-hazard laboratories (e.g. flames lab, slinks lab, pressure labs etc.) available within the buildings. These laboratories are restricted access areas. Only authorised staffixduents familiar with and trained in experiments performed are allowed to access and work in these laboratories. Engineering - All work involving chemicals is to be performed in furne cupboards fit for work with hazardous chemicals by Australian Standards. The number of furne cupboards in a wet chemistry laboratory depends on frequency of work, available space, and existing infrastructure. The air flow is provided either by strobic first that linked to the furne cupboards in a amanifold system that runs through the buildings, or stand-alone extraction fans for each furne cupboard. Each laboratory is completely (physically) segragated from adjacent laboratories and office areas. Permanently installed safety showers and eye wash stations in wet chemistry areas. Designated storage cabinets for chemicals. Gas cabinets with extraction spigots inside for cylinders being used (alternatively, usage of up to D-size cylinders inside furne cupboards). Some buildings have sinks connected to a neutralisation pit that lab sinks are connected to. Ventillated space for temporary chemical waste storage. Administration - ANU- and School-wide procedures, policies and guidelines such as chemical management, commensed gases, hazardous waste management, HF handling that address a number of major chemical hazards and how to safely deal with them, and they also prescribe individual risk assessments being required by each worker prior to performing any experiment/reaction. Local induction and training and/or relevant existing background for handling high hazard chemicals. ANU courses (e.g. chemical	"Work Health and Safety Act 2011 (Clh) ///- Work Health and Safety Regulations 2011 (Clh) ///- Chapter 7 - Hazardous Chemicals ///- Work Health and Safety Regulations 2011 (Clh) ///- Chapter 7 - Hazardous Chemicals ///- Scheduled Carcinogenic Substances (schedule 10) ///- Schedules 11, 12, 13, 14 ///- Medicines, Poisons and Therapeutic Goods Act 2008 ///- Auditorial Industrial Chemicals Michigation & Assessment Steme (NICNAS) ///- Industrial Chemicals (Notification & Assessment) Act 1989 ///- Dangerous substances Act 2004 (ACT) ///- Chemical Weapon conventions. Standards and GoPs: **Australian Dangerous Goods // AS 1940 The Storage and Handling of Flammable and Combustible Liquids /// AS 2567 Laminar Flow Cytotoxic Drug Sa Cabinets /// AS IASS 24243 2: Safety in laboratories Storage of Chemicals /// AS ANZS 24243 2: Safety in laboratories Othericals /// AS ANZS 24243 2: Safety in laboratories Othericals /// AS ANZS 24243 2: Safety in laboratories Othericals /// AS ANZS 24243 2: Safety in laboratories Othericals /// AS ANZS 24243 2: Safety in laboratories Storage of Chemicals /// AS ANZS 24243 2: Safety in laboratories Storage of Chemicals // AS ANZS 2424 3: Safety in Laboratories Storage of Chemicals // AS ANZS 2425 The Storage and Handling of LP Gas // AS AS 456 identification of the Contents of Pipes, Conduits and Dural AS ANZS 2425 The Storage and Handling of the Othericals // AS ANZS 2475 Handling and Destruction of Dural AS ANZS 2425 Flam Storage and Handling of the Othericals // AS ANZS 2475 Handling and Destruction of Dural AS ANZS 2425 Flam Storage and Handling of the Companies (Impact and Handling of the Companies // AS ANZS 2475 Handling and Destruction of Dural AS ANZS 2425 Flam Storage and Handling of the Companies (Impact and Handling of Capitals on of Assessment of Handling of Capitals // AS ANZS 2475 Handling and Destruction of Assessment of	RARE e	CATASTROPHIC	MEDIUM (12)	YES		
	Chemicals such as mercury, cyanides, carcinogens, heavy metals.	Environmental pollution (business as usual) leading to substantial damage to waterways and water purification plant and/or illness to the community if exposed to contaminated water or air; intense negative reputation (media)	LIKELY	CATASTROPHIC	EXTREME (24)	Elimination - Substitution - Wherever possible, alternatives to environmentally hazardous chemicals are to be used (e.g. one-way valves with pressure setpoint instead of mercury bubblers, alcohol thermometers instead of mercury bubblers, alcohol thermometers instead of mercury thermometers). Isolation - Chemicals should be handled in laboratories that have no connection to stormwater or direct connection to sewers. In some buildings, drains from sinks within laboratories are connected to a neutralisation pit. Engineering - Work with toxic votatiles to be done in purposely built scrubbed fume cupboards where applicable. In some buildings, sinks are connected to a neutralisation pit for pH adjustment prior to release into waste water. Administration - Australian Standards (e.g. lab safety series 2243), Codes of Practice (e.g. managing risks of hazardous chemicals in the workplace, labeling chemicals, SDSs, first ald), ANU- and School-wide safety policies and regulations, all of which address a number of major chemical hazards and regulations, all of which address an unmeen of major chemical hazards and training and/or relevant existing background for handling high hazard chemicals. Risk assessments prior to performing any experiment/reaction and supervisor sign-off for experiments involving chemicals of high hazard (e.g. strong corrosives, toxics, pyrophorics), prior to commencement. Transport of chemicals to be done in secondary containment. Liquids to be stored in secondary containment (spill trays), Regimented chemicals as tostored in secondary containment (spill trays), Regimented chemical wasted disposal program (funded by Individual budget areas to 100%) through external contractors on an appropriate pick-up cycle to minimismis estock of waste chemicals. Spill kits located in main areas where chemicals are being handled, including near stores and loading dock. "No chemicals down the sirk" policy (induction, notices, TOs).	As under "Chemicals" above	UNLIKELY	CATASTROPHIC	HIGH (19)	NO	Toxic components not being tested for. Neutralisation pit adjusts pH only, i.e. not a means of destroying/capturing toxic components.	
	Chemicals such as mercury, cyanides, carcinogenics, heavy metals, products forming under heat (fire) such as phosgene, CO	Enviornmental pollution (in an emergency scenario) leading to substantial damage to waterways and water purification plant and/or illness to the community if exposed to contaminated water or air; significant negative reputation (media)	POSSIBLE	CATASTROPHIC	EXTREME (23)	Elimination - Substitution - Isolation - Engineering - Fire detection and sprinkler system to detect early signs of fire and prevent the spread of fire. Compartmentalised experimental areas (segregated laboratories). In some buildings, there are no floor drains in laboratories to avoid spilled material reaching waterways. In some buildings, floor drains are connected to a neutralisation pit. Administration - Australian Standards (e.g. laboratory design, emergency control), Codes of Practice (e.g. managing risks of hazardous chemicals in the workplace, labeling chemicals, SDSs), ANU- and School-wide safety policies and regulations, all of which address a number of major chemical hazards and related infrastructure and how to safety handle those. Moving away from large stocks of chemicals such as DGC3 and instead purchasing smaller quantities of chemicals at a higher frequency as the chemicals are needed to reduce holdings. Minimise holdings of chemicals such as flammable gases and liquids to a minimum (part of safety) inspections). Segragation of incompatible materials. Strict guidelines about naked flames (prohibited under normal circumstances, high-risk category if used in association with DGC3s). Strict guidelines about distillation setups. Secondary containment for liquids to avoid spread of chemicals in the event breakage of primary containment. CMS for location of hazardous chemicals. School-wide annual clean-up involving all reasearch groups, part of which serves to identify chemicals that have exceeded their safe life cycle. ECO including technical staff familiar with laboroatory environment. ANU crisis managment structure (campus evacuation, mass communication of emergencies on campus). PPE - N/A	As under "Chemicals" above	RARE	CATASTROPHIC	MEDIUM (12)	YES	This is hard to probe. The 2005 fire at RSC is an example of an emergency situation that would have relesaed all sorts of toxic combustion products into the air and that were not contained. Whether this had an effect on people present or people in the wider community is not clear.	

equipme	iicals and ment of ity and legal ern	Misuse (criminal intentions, unintentional release to community) leading to illness and/or negative reputation (media)	ALMOST CERTAIN	MAJOR	EXTREME (22)	Elimination - Substitution - Isolation - Isolation - Engineering - Controlled building acces. Administration - Code of practice (chemicals of secuirity concern), ANU policies, procedures and guidelines (chemicals of security concern). Stocktake/inventory (CMS). Controlled purchasing (fixed delivery points). Controlled (locked) storage locations (e.g. safe or cabinet) for certain types of chemicals (cyanides, arsenic, scheduled carcinogens, HF). Highlighting risk during induction and communicate importance of preventing unauthorised access (e.g. piggy bagging, bringing external people on site 'friends'). Staff challenging unknown people found inside building. Complete curfew at times when no staff is on site for controlling access/challenging unauthorised access (vigilance). PPE	As under "Chemicals" above	POSSIBLE	MAJOR	HIGH (18)	NO	Raise access restrictions, more regimented user control, wider range of chemicals under tighter access restrictions.	
pyrophor flammab	icals is highly control includes, or able gases and a t, alkali metals	Fire, explosion, violent reaction, lue to wrong handling, storage with incompatible materials, mixing of incompatible hemicals, or decomposition eading to substantial injury, liness or death of building occupants. Illness of the bounding infrastructure, which and/or substantial damage to he building infrastructure, which ould potentially put in excess of 200 workers out of work for significant periods of time, i.e. significant loss of productivity and research output, leading to educed income. And/ or negative reputation (media).	LIKELY	CATASTROPHIC	EXTREME (24)	Elimination - Substitution - Wherever possible, alternatives to hazardous chemicals for research purposes are being used over hazardous chemicals. Isolation - Where highly hazardous chemicals are deemed necessary, isolated high-hazard laboratories (e.g. flames lab, stinks lab, pressure lab) available within the building are to be used. These laboratories are to be used by one person at a time only. Chemical waste is stored in a designated storage location outside the building. All liquids are doubly contained (trays, stillages with liners) Engineering - Fire detection (including heat sensors within furne cupboards) and sprinkler system to detect early signs of fire and prevent the spread of fire. Compartmentalised experimental areas (segregated laboratories), Fridges equipped with external thermostats. Flammable cabinets for the majority of DGC3. Bulk solvents stored external to the main building. Fridges and freezers equiped with external thermostats. Designated ventillated (and/or external) storage location for chemical waste. Administration - Moving away from large stocks of chemicals such as DGC3 and instead purchasing smaller quantities of chemicals at higher frequency as they are needed to reduce holdings. Minimise holdings of chemicals such as flammable gases and liquids to a minimum (part of safety inspections). Segragation of incompatible materials. Strict guidelines about naked flames (prohibited under normal circumstances, high-risk category if used in association with DGC3s). Strict guidelines about distillation setups. Secondary containment for liquids to avoid spread of chemicals in the event breakage of primary containment. Controll risk through keeping scale small. Emergency Control Organisation (ECO) including senior chemists and SCBA trained staff. Regular (e.g. fortnightly) disposal of chemical waste to minimise holdings of chemical waste unless fairly neat solvent waste mixtures (e.g. from tPPC) are generated and generated at a rate that renders larger containers most practicable, maximu	As under "Chemicals" above	RARE	CATASTROPHIC	MEDIUM (12)	YES		
Non-ion radiation (UV, RF)	ion	Eye injury or illness (cancer), fire. And/ or negative reputation (media)	POSSIBLE	MAJOR	HIGH (18)	Elimination - Substitution - Dipping solutions rather than UV lamps can be used in some cases to develop TLCs. Isolation - UV lamps are operated in enclosures preventing UV radiation to leak out. Engineering - Laminar flow cabinets have interlocks that prevent operation of the UV light unless UV-blocking shields are in place. High-power (10-1000W) UV lamps for UV-activated reactions are operated in specially designed housings with various interlocks that respond to unauthorised opening of the housing, lack of cooling supply, lack of ventilation (air flow) or heat development within the housing Eximer laser beam (UV) running inside perspex housing that cuts out all UV. Administration - Internal training based on the SOP is mandatory for all users of UV reaction chambers. Exposure limits from UV sources are determined together with ANU WEG. All UV sources are registered on the ARPANSA register for radiation sources (SIWB). Most UV sources are for TLC viewing. Leakage testing on newly installed equipment (e.g. flow chemistry reactor, reactor for UV-activated reactions). PPE - Nitrie gloves cut out the UV light emitted from lamps used for TLC viewing.	Legislation: *Work Health and Safety Act 2011 (Cth)// Work Health and Safety Regulations 2011 (Cth)// Australian Radation and Nuclear Safety (ARPAN Act// ARPANS Regulations// Nuclear Non-proliferation (Safeguards) Act 1987 Standards and CoPs: *HB 9 Occupational Personal Protection// Radiation Protection Standard for Occupational Exposure to Ultraviolet Radiation (Commonwealth)//	RARE	MAJOR	MEDIUM (11)	YES		
	power Lasers	Serious eye injury, skin injury (burns), fire leading to serious injury or death; chemical exposure (fluorine) leading to serious injury or death, and/ or negative reputation (media).	LIKELY	CATASTROPHIC	EXTREME (24)	within its own ventilated cabinet, with shut-off solenoid valves that are activated with low air flow. Other style biological safety cabinets can now be replaced with double-interlocked ones (ARPANSA registration no longer required). Administration - Internal laser training/skill assessment through Laser Safety Officer mandatory for all users of class III and IV lasers. ANU laser course and laser eye exam mandatory for all ANU staff and students. ARPANSA regulations. ANU radiation policy and procedure, including approval for new work. Appointed laser safety officers in loca areas. Safety consultants with relevant responsibilities at ANU level. Experiments to be designed in a way that avoids laser beams to leave the table, and run to to be used around the laser tables (e.g. proper metallic beam dumps and shutters used to intercept beams, metallic sheids around the table). Laser tables with open beams are equipped with non-reflective (mate) components such as side sheids and such assers are	Standard for Occupational Exposure to Ultraviolet Radiation [Commonwealth] —///— Radiation Protection Series (ARPANSA) —///— Radiation health Se (ARPANSA) —///— Occupational Health and Safety Code of Practice 2008 —///— Refer to "Plant" classification for plant standards/codes/Guidance ANU Policies and Procedures:	RARE	CATASTROPHIC	MEDIUM (12)	YES		

Ionising radiation from X-ray machines	Serious injury or illness leading to death on long or repeated exposure. And/ or negative reputation (media).	POSSIBLE	CATASTROPHIC	EXTREME (23)	monitoring). Individual training is provided for each user for each instrument. Interlock override keys are kept in a key safe, with limited senior staff having access to the safe. Safety consultants with relevant responsibilities at ANU level. Where labs are used for various purposes, lights outside the room indicate when X-ray instruments inside the room are being operated. Regular leak checks on each instrument. Repairs are	Legislation: *Work Health and Safety Act 2011 (Cth) — ///— Work Health and Safety Regulations 2011 (Cth) — ///— Australian Radation and Nuclear Safety (ARPAN Act — ///— ARPANS Regulations — ///— Nuclear Non-proliferation (Safeguards) Act 1987 Standards and Cops: *AS 2243.4 Safety in Laboratories — Ionizing Radiations — ///— HB 9 Occupational Personal Protection — ///— Recommendations for Limiting Exposu to lonizing Radiation and National Standard for Limiting Occupational Exposure to lonizing Radiation (Dommonwealth) — ///— (Area of Practice for the St.) *Transport of Radiation (and National Standard for Limiting Occupational Exposure to lonizing Radiaction (Dommonwealth) — ///—— (Area of Practice for the St.) *Transport of Radiactive Material (Commonwealth) — ///—— (Area of Practice of The St.) *Transport of Radiactive Material (Commonwealth) — ///—— (Area of Practice of The St.) *Transport of Radiactive Material (Commonwealth) — ///—— Redation Protection (Lommonwealth) — ///—— Recommendations for intervention in Emergency Studies for the Standard Developed (Commonwealth) — ///—— Code of Practice and Safety Practice of The Standard to Protection in Standard for Cocupational Exposure (Dommonwealth) — ///—— Code of Practice and Safety Guide for Radiation Protection in Standard for Cocupational Exposure of Ultraviolet Radiation (Commonwealth) — ///—— Code of Practice of Radiation (Commonwealth) — ////—— Code of Practice of Radiation (Commonwealth) — /////—— Code of Practice of Radiation (Commonwealth) — //////—— Safety Guide for the Management of Nature (Commonwealth) — //////— Code of	re afe bn re RARE	CATASTROPHIC	MEDIUM (12)	YES		
Cryogenic liquids and solids such as liquid nitrogen and helium and solid carbon dioxide	Skin and eye injury (cold burns), explosion (vessels rupturing, condensing liquid oxygen), asphyxiation	POSSIBLE	CATASTROPHIC	EXTREME (23)	Substitution - Bulk source of liquid nitrogen (storage tanks) stored outside buildings in locked cages with limited access (maintenance contractors, workshop/emergency staff). Bulk dry ice stored in external areas (e.g. at loading dock). Engineering - Pressurised 200L dewars for decanting LN2 for every-day use in labs within buildings equipped with pressure relief valves and preferably dispensing nozzles (minimising splashes). Solenoid valves with dead-man switch allow remote operation of the valves and prevent accidental release of LN2. Internal decanting areas often equipped with oxygen sensors to warn users of oxygen deficient atmosphere. Particularly in newer buildings, areas where cryogenics are located or potentially be used and that have limited ventilation (e.g. codi rooms, physchem laboratories, NMR rooms) are equipped with aarmed oxygen sensors. Somer areas (e.g. NMR suite) equipped with ventillation system that kick in once oxygen levels drop below critical level (18.5%). We chemical laboratories are equipped with furm eupboards that prevent formation of inert gas pockets (low-oxygen environment) within the laboratories. Negative pressure inside the labs prevents gases to dissipate into adjacent corridors or office areas. Administration - ANU training module on compressed gases and	 Labelling of Workplace Hazardous Chemicals – Model Code of Practice, Safe Work Australia, September 2015 — ///- Preparation of Safety Data Shee for Hazardous Chemicals, Model Code of Practice, Safe Work Australia, February 2016, ANU Policies and Procedures: 	RARE	CATASTROPHIC	MEDIUM (12)	YES		
Vacuum or high- pressure vessels (gas cylinders, dewars, sealed reaction vessels)	Serious injury or death following explosion/rupturing/implosion ; and/ or negative reputation (media)	POSSIBLE	CATASTROPHIC	EXTREME (23)	Elimination - Use non-pressurised gas if pressurised gas is not needed (e.g. use hydrogen generator rather than pressurised gas cylinder) Substitution - Actively aim for using smallest possible yet reasonably practicable cylinder size so that large cylinders are avoided. Isolation - Bulk source of liquid nitrogen (2000L storage tank) stored outside the building in locked cage with limited access (maintenance contractors, RSC workshop/emergency staff). Stock of pressurised 5-size cylinders stored in designated areas outside the building (external H2 and O2 cages, external ventillated room for nitrogen/argon/helium cylinders). Cylinders within the building are normally stored outside the laboratories in purpose-built, vented gas cabinets; the cabinets allow easy connection of the cylinders to a main valve followed by a single stage regulator, from where gas lines are plumbed into the fume cupboards inside the labs via fixed stainless steel lines (most common gases are argon and nitrogen). Designated pressure laboratories available for setting up reactions under pressure. Engineering - Pressurised 200L dewars for decanting LN2 for every-day use in labs within building 137 equipped with pressure relief valves. The regulators inside the gas cabinets are fixed to the wall, i.e. transportation of cylinders with regulators attached not likely to occur. Flammable and oxidising gaseo only to be used if one-way valves/flashback arrestors are in place (all permanent lines fitted with such valves). Administration - Proper procedure for retrieving and connecting gas cylinders (e.g. buddy system, designated trained people). Trolleys must be	Legislation: -Work Health and Safety Act 2011 (Cth) — ///— Work Health and Safety Regulations 2011 (Cth) Standards and CoPs:	RARE	CATASTROPHIC	MEDIUM (12)	YES		
Mechanical impact (heavy weights, repetitive tasks, awkward posture, high force, vibration, twisting/bending)	Short-term, long-term or permanent injury or disability (limbs, joints, back)	LIKELY	MAJOR	EXTREME (20)	Elimination - Substitution - Substitute one large unit for several smaller units (e.g. 5L waste containers instead of 20L drums). Use lighter materials over heavier ones (e.g. carbon fibre cylinders over steel cylinders). Make use of state-of- the-art equipment (smaller and/or fewer components, lighter materials). Isolation - Engineering - Mechanical transport and lifting aids (forklift, trolleys, vehicles, stackers, walkers, platform ladders, hoists, gantries, cranes, lifting tackles) to move heavy load. Ergonomic light-weight pipettes for frequent	Legislation: - Work Health and Safety Act 2011 (Cth) /// Work Health and Safety Regulations 2011 (Cth): Part 5 - Manual Handling. Standards and CoPs: - National Standard for Manual Tasks /// Occupational Health and Safety Code of Practice 2008 /// National CoP of musculoskeletal disorders for performing manual handling tasks at work /// National CoP for Manual Handling (NOHSC:2005 (2009) /// National Standard for Manual Tasks // Model CoP- Hearded CoP- Heardedox Manual Tasks // How to manage work health and safety risks // // National Standard for Manual Tasks //	om POSSIBLE	MAJOR	HIGH (18)	NO	Stronger promotion of proper techniques, and ensure required infrastructure is available and being used adequately.	

Elimination - Substitution - Substit		
Elimination - Substitution - Substit		
Dorp in safety standards, lack of expertise, leading to incidents through poor technique; equipment damage due to wrong handling; loss of time through loss of efficiency California C	RREST LOSS. Ensure sufficient verlap between outgoing and incoming staff. Ensure spacity/resources for carrying increasing administrative burden (write/review procedures and risk sessments) is warranted in all budget areas.	
Uncontrolled Emergency (fire, chemical spill, power details) Emergency (fire, chemical spill, power details) Engineering - Automatic emergency evacuation in a fire scenario (detection, amouncement/evac alam, fire bringade) Centrality alammed critical plant estructure (e.g. cooling water pumps, heat sensors, oxygen ensors, safety showers). Gasquard system for automatic neutral gas shut-off. Administration - ECO communication during emergency via 2-way radios (independed etc.) gibly flexible). ECO (ind. SDR) Export cituage, power cituage, power cituage, and coverage). POSSIBLE CATASTROPHIC CATASTROPHIC CATASTROPHIC CATASTROPHIC EXTREME C3) Initiation - Subdition -		
Noise (heary machinery, plant equipment, pressure vessels) Hearing loss LIKELY MODERATE HIGH (16) Elimination - Substitution - Isolation - Plant equipment in designated areas (plant rooms), heavy machinery in workshops. Engineering - Mufflers (e.g. LN2 tank). Shock absorbers (e.g. rubber pads for pumps). Administration - Equipment maintenance (reduction of noise generated from scraping)/loose parts). Warning signage. Risk assessment. Regularly changing tasks/job vairely (noise level not permanent). PPE - Ear muffs/ear plugs. Elimination - Substitution - Isolation - Plant equipment in designated areas (plant rooms), heavy machinery in workshops. Engineering - Mufflers (e.g. LN2 tank). Shock absorbers (e.g. rubber pads for pumps). Administration - Equipment maintenance (reduction of noise generated from scraping)/loose parts). Warning signage. Risk assessment. Regularly changing tasks/job vairely (noise level not permanent). PPE - Ear muffs/ear plugs. Elimination - Substitution - Isolation - Work Health and Safety Act 2011 (Cth)//I/ Work Health and Safety, Rehabilitation and Compensation Act 1986. Act		
Elimination A so Il Maschi 2016, no RSC Research Croups are performing with that throwbers any under the following in the path has been made required courses. Substitution - A lot of work that used to require radioache marking in the path has been made required to counted any of the counter of the counte		

				•	